



Kixx Outboard 2T

Two-Stroke Outboard Motor Oil

TC-W3 RECOMMENDED

DESCRIPTION

Premium performance, two-stroke, marine outboard motor oil formulated with a special ashless additive system. Pre-diluted with special solvent to facilitate mixing easily with gasoline at all temperatures. Designed for engines requiring NMMA TC-W3[®] lubricants, operating in all service conditions.

APPLICATIONS

- All water-cooled, two-stroke, marine outboard engines, including the latest designs under warranty protection
- Oil-injected engines
- Air-cooled, two-stroke engines where NMMA certified oils are specified

PERFORMANCE STANDARDS

- National Marine Manufacturers Association (NMMA) TC-W3[®] Recommended
- NMMA TC-WII[®], TC-W[®] Recommended

CUSTOMER BENEFITS

Maintains high power output

The special blend of ash-less additive system provides superior piston cleanliness and protection against ring sticking by minimizing deposit formation, thus maintaining combustion efficiency and protecting against power loss.

Trouble-free operation

The ash-less additive system ensures that ash-induced deposits are not formed in the combustion chamber, eliminating the risk of destructive pre-ignition.

Maximizes spark plug life

The ash-less additive system reduces spark plug fouling under all operating conditions.

KEY PROPERTIES

SAE Grade (J1536)	F/M 3
Ash, mass %	<0.01
Viscosity, mm ² /s @ 40°C	45.25
Viscosity, mm ² /s @ 100°C	7.59
Viscosity Index	135
Pour Point °C	-39
Package (Liters)	1,200