Fully Synthetic

Kixx D1 RV

High grade diesel engine oil providing excellent protection

ACEA C3-12, API SN/CF MB 229.31/229.51 BMW LL-04 RECOMMENDED



DESCRIPTION

Kixx D1 RV is formulated with the latest VHVI synthetic base oil combined with additive technology that produces minimum sulfated ash, phosphorous and sulfur contents to meet the requirement of low SAPS oil. Kixx D1 RV is suitable for passenger car mounted with gasoline or diesel engines, as well as SUV and RV. Kixx D1 RV maintains engine durability while helps in extending the life of DPF and helps in increasing DPF performance by using additive of minimum sulfated ash contents. Kixx D1 RV also helps extending the life of emission after-treatment device such as SCR by introducing low phosphorous and sulfur content additive technology.

APPLICATIONS

- SUV and RV equipped with DPF, SCR and other emission aftertreatment system where an ACEA C3 performance engine oil is required.
- Light duty diesel engines and gasoline direct injection engines.
- Passenger cars where the manufacturers recommend API SN spec oils.
- Vehicles that requires MB, BMW specification performance.

PERFORMANCE STANDARDS

- ACEA C3-12
- API SN/CF
- MB 229.31, 229.51 / BMW LL-04 Recommended

KEY PROPERTIES

SAE Grade	5W-30	5W-40
Density, kg/L @15°C	0.848	0.8543
Kinematic Viscosity, mm ² /s @ 40°C	69.2	89.5
Kinematic Viscosity, mm ² /s @ 100°C	12.3	14.9
Viscosity Index	178	179
Pour Point °C	-42	-42
Flash Point °C	228	238
Package (Liters)	5, 200	200