

Fully Synthetic

Kixx ATF DX-VI

Top Performance Low Viscosity Automatic Transmission Fluid

GM DEXRON®-VI, FORD MERCON LV,
JASO 1A-LV



DESCRIPTION

Kixx ATF DX-VI is a premium performance, low viscosity multi-vehicle fluid for modern automatic transmissions, which is blended with synthetic base stocks and advanced high performance additives. It is specially designed to provide improved fuel efficiency and excellent shudder control performance. Kixx ATF DX-VI is officially approved for use by GM and meets or exceeds the requirements of latest OEM specifications such as Ford MERCON LV, Toyota WS, Nissan Matic S, Hyundai SP-IV/SP-IV-RR. It is also suitable for most modern 6+ speed automatic transmissions.

PERFORMANCE STANDARDS

Auto Maker	Specification	Auto Maker	Specification
GM	DEXRON® VI Approved	Mercedes / Daimler	MB 236.10/11/12/14/15
	DEXRON® III G, IIIH DEXRON® II, IID, IIE		MB 236.3/4/15/6/7/8/81/9/91
Toyota / Lexus	Type D-III	Suzuki	3314, 3317
	Type T, T-III, T-IV Type WS (JWS 3324)	Allison	TES-295/353/389
VW / Audi	G 052 533/055	Volvo	P/N 1161521, 1161540, 1161640
	G 052 025 (A2)	Ford / Lincoln	WSS M2C 922A1
	G 052 990 (A2)		WSS M2C 924A
	G 055 025 (A2)	Honda	ATF-Z1(except in CVTs) ATF Type 3,0/3,1
G 055 540 (A2)	Mazda	JWS 3317, Type T-IV D-III, M-III, M-V, FZ, F-1	
ZF	G 060 162 (A1, A2, A6)	Hyundai / Kia	SP-III, SP-IV, SP-IV RR ATF Reo-1K
	Lifeguardfluid6, 8 TE-ML 03D/04D/11A/14A/16L/17C		JWS 3309 T-4 NWS 9638 T-5
BMW	ATF-3+	Mitsubishi	Diageen SK, AW, SP-IV Diageen J2, J3
	JWS 3309 (T-IV) LA2634, LT71141		Diageen ATF-PA
	7045E, ETL-8072B	Nissan	Matic-D, Matic-J, Matic-K Matic-S, Matic-W
	83 22 0 142 516 83 22 2 152 426 83 22 2 305 397		JASO


CUSTOMER BENEFITS

- OEM approved and licensed by GM(DEXRON®-VI).
- Improved fuel efficiency and shudder control performance.
- Excellent transmission cleanliness and durability by oxidation/thermal stability.
- Good start operation in cold climates thanks to its excellent low-temperature fluidity.
- Excellent friction performance and shift feel durability for comfort transmission shift.
- Exceptional wear and corrosion performance for long equipment life.


KEY PROPERTIES

Density, kg/L @15°C	0.864
Kinematic Viscosity, mm ² /s @ 40°C	30.3
Kinematic Viscosity, mm ² /s @ 100°C	6.0
Pour Point °C	-52
Flash Point °C	224
Brookfield Viscosity, cP @-20°C	864
Brookfield Viscosity, cP @-40°C	12,100
Package (Liters)	1, 4T, 200

UNIQUE FEATURES



- At least 20% longer than Competitor
- At least 30% longer than Toyota T-III



- Kixx ATF DX-VI consistently within JASO limit