

Fully Synthetic



# Kixx ATF Multi

Top Performance Multi-vehicle Automatic Transmission Fluid

JASO 1A, GM DEXRON®-III, TOYOTA T-IV, HYUNDAI SP-III/SP-IV

## DESCRIPTION

Kixx ATF Multi is a high-performance, high-quality multi-vehicle fluid for automatic transmissions. (Applicable for Slip controlled lock-up clutch) It is a specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications requiring Hyundai SP-III, SP-IV, GM DEXRON® III, Ford MERCON®, Toyota T-IV and WS. In addition, it meets the requirements of European OEM's like Volvo CE 97340 and MB, BMW, VW, ZF 4, 5, 6 and 8-speed automatic transmission specifications. Kixx ATF Multi is a special blend of high quality base stocks with an advanced additives system for use as a Service-Fill.

## PERFORMANCE STANDARDS

Auto Maker	Specification	Auto Maker	Specification
VW / Audi	G 052 162 (ZF Lifeguard 5)	Hyundai / Kia	Dex-III, SP-II
	G 055 162-A2, A6 (ZF Lifeguard 6 Plus)		JWS 3314, NWS 9638
	G 060 162 (ZF Lifeguard 8)	SP-III, SP-IV, SP-IV M, SP-IV RR	
	G 052 990	ATF RED 1, RED 1K	
	G 055 025-A2 (JWS 3309)	ATF 3403 JLM20238	
Mercedes Benz	MB 236.1, 236.2, 236.3	Jaguar	ATF 3403-M115
	MB 236.5, 236.6, 236.7	ATF LT71141, ZF 5HP 24	
	MB 236.8, 236.9	JASO	M315-2013 1A
BMW	7045E, ETL-8072B	M315-2013 2A	
	JWS 3309 (T-IV)	Mazda	ATF 3317
	LT71141 (ZF 5 HP 18FL/19FL/24A/30)	ATF D-II, F-1, FZ	
Ford	MERCON®, FNR5	ATF M-III, M-V, N-1, S-1	
	WSS M2C138CJ, M2C166H	Mitsubishi	Diaqueen ATF PA
	WSS M2C 922A1, 924A	Diaqueen AW	
Fuso	WSS M2C 938A	Diaqueen J2, J3, SK	
	ATF-A4	Diaqueen SP-II, SP-III, SP-IV	
	ATF-II	Nissan	Matic Fluid C, D, J
GM	ATF-SP III	Matic Fluid K, S	
	DEXRON®-II, IID, IIE	Porsche	ATF 3403-M115
	DEXRON®-III, IIIH	T-IV (JWS 3309)	
Honda	GM/GMC/Opel/Saturn VI, AW1	ZF 5HP 19FL, 5HP 20, LT71141	
	ATF Ultra II, DW-1	Subaru	ATF, ATF 5AT, ATF HP
	ATF-Z1(except in CVTs)	Suzuki	ATF 2326, ATF 2384K
Chrysler / Dodge	Type 3.0, Type 3.1	ATF 3314, ATF 3317	
	ATF+, +2	JWS 3309	
	ATF +3(MS 7176E), +4(MS 9602)	Toyota	ATF D-II, D-III, T-III, T-IV(JWS 3309)
Isuzu	JWS 3309 (T-IV)	ATF WS(JWS 3324)	
	Besco ATF-II	ZF	4~9 speed transmission
	Besco ATF-III	TE-ML 05L, 09, 11A, 11B, 21L	
JEEP	ATF+3, +4	Shell	3403, M115, LA 2634
		Texaco	7045-E, 8072B, N402

## CUSTOMER BENEFITS


- Excellent anti shudder protection.
- Oxidation and thermal stability
- Provides high foam stability.
- Provides good start operation in cold climates thanks to its excellent low-temperature fluidity.
- Provides more stable friction property.
- Use for most 4~8 speed vehicles.

## KEY PROPERTIES

Density, kg/L @15°C	0.845
Kinematic Viscosity, mm <sup>2</sup> /s @ 40°C	35.6
Kinematic Viscosity, mm <sup>2</sup> /s @ 100°C	7.0
Pour Point °C	-49
Flash Point °C	220
Brookfield Viscosity, cP @-20°C	875
Brookfield Viscosity, cP @-40°C	14,960
Package (Liters)	1, 4, 4T, 20, 200

## UNIQUE FEATURES

Kixx ATF Multi has demonstrated superior oxidation stability performance in various industrial requirements.



Kixx ATF Multi provides Excellent Shear Stability performance exceeds the requirements of European OEMs.

