

Fully Synthetic



# Kixx PSF

Top Performance Power Steering Fluid

ALLISON C-4, DEXRON®-III

## DESCRIPTION

Kixx PSF is specially designed for use in power steering system applications over a wide temperature range, which is also meets the service requirements of many OEMs such as DEXRON®-II, DEXRON®-III, Allison C-4, etc. It is a high quality performance which meets oxidation resistance, low temperature fluidity, appropriate friction performance, high shear stability.

## APPLICATIONS

- Power steering units (Passenger cars, trucks, buses, etc) for service-fill product is specified as DEXRON®-II, DEXRON®-III fluid.

## PERFORMANCE STANDARDS

- General Motors DEXRON®-II, DEXRON®-III
- Allison C-4

## CUSTOMER BENEFITS

- Ensures long life-time.
- Provides high foam stability.
- Provides excellent corrosion prevention.
- Provides good start operation in cold climates by excellent low-temperature fluidity.
- Provides more stable friction property.

## KEY PROPERTIES

Appearance	Red
Density, kg/L @15°C	0.844
Kinematic Viscosity, mm <sup>2</sup> /s @ 40°C	34.3
Kinematic Viscosity, mm <sup>2</sup> /s @ 100°C	7.2
Viscosity Index	180
Pour Point °C	-48
Flash Point °C	212
Brookfield Viscosity, m Pas @-20°C	1,050
Brookfield Viscosity, m Pas @-40°C	11,000
Package (Liters)	1