



Kixx RA Coolant

Top Performance Radiator / Coolant

DESCRIPTION

Kixx RA Coolant is a premium quality, ethylene glycol based amine-phosphate type coolant, which is pre-mixed with ionized water (80%). It is designed primarily to meet the corrosion protection requirements of late model car engines having significant amounts of aluminum in their construction. It is dyed a distinctive color for ready identification.

APPLICATIONS

- Primarily recommended for late model passenger car and light commercial vehicle engines where enhanced protection of aluminum heat-rejecting surfaces is required. It can also be used in certain cast iron, heavy-duty diesel engines, which operate without supplemental coolant additives(SCAs).
- Kixx RA Coolant is a pre-diluted coolant with clean water. Its freezing point is about -8°C, boiling point increases about 3°C.

PERFORMANCE STANDARDS

- ASTM D 3306
- KS M2142
- JIS K2234

CUSTOMER BENEFITS

- Protects cooling systems from corrosion and deposits.
- Provides higher boiling point for protection against engine overheating.
- Prevents coolant freezing.
- Maximizes aluminum engine component life.
- Long service life.

KEY PROPERTIES

Test Item		Specification	Typical Value
Specific Gravity	Undiluted	1.020~1.028	1.028
Freezing point, °C	Undiluted	-7 max	-8.1
Boiling point, °C	Undiluted	100 min	103
Foaming, ml	Undiluted	10 max	0
PH	Undiluted	6.0~11.0	8.24
Package (Liters)			0.5, 4, 200